

VAPORIZZATORI GPL AD ACQUA Tipo feed-back

LPG WATER VAPORIZERS



VAPORISATEURS GPL À EAU

ATEX

COPRIM - ITALY



VAP.	Cod.
100 Kg/h	1.02.66
200 kg/h	1.02.68
300 Kg/h	1.02.70
500 Kg/h	1.02.72
1.000 Kg/h	1.02.74
2.000 Kg/h	1.02.76



temperatura progetto TS - 40 +120 °C

design temperature - température du projet

pressione progetto PS 40 bar

design pressure - pression du projet

SPECIFICA

- Manometro Ø60 25 bar con contatti
- Valvola di sicurezza 1/2" 18 bar
- Termometro -20 + 120 °C
- Valvola di sicurezza acqua 1,5 bar
- Valvola di sfiato aria
- Pressostato

Entrata acqua 1"
Uscita acqua 1"

SPECIFICATION

- Manometer Ø60 25 bar with contact
- safety valve 1/2" 18 bar
- Thermometer -20 + 120 °C
- Water safety valve 1,5 bar
- Air breather valve
- Pressure switch

Inlet water 1"
Outlet water 1"

DETAIL

- Manomètre Ø60 25 bar
- Valve de sécurité 1/2" 18 bar
- Thermomètre -20 + 120 °C
- Soupape de sécurité eau 1,5 bar
- Soupape de pugeur d'air
- Pressostat

Entrée eau 1"
Sortie eau 1"